



PRODUCT NUMBER: 2008010

## POWERCOAT® 080-10 BUTYL

Protection against aggressive chemicals, acetones, MEK and esters. Gaz tight.

**Honeywell**

### Overview

**Reference Number**

2008010

**Product Type**

Gloves

**Range**

Chemical Protection

**Line**

Heavy chemical

**Brand**

Honeywell

**Brand formerly known as**

SPERIAN

**Industry**

- Offshore
- Petro-chemical
- Water treatment

**Product Use**

Protection against aggressive chemicals, acetones, MEK and esters. Gaz tight.

### Features & Benefits

**Feature**

Unsupported Butyl® glove

Rolled edge

Smooth inside

**Benefit**

COMFORT

More flexible than natural latex, Butyl® gloves provide good dexterity.

Remains supple from -30°C up to +50°C.

Smooth inside to ease donning and duffing.

RESISTANCE

Butyl offers resistance to many solvents, acids and medium concentrated bases.  
 It resists to ozone and heat.  
 Gaz tight.  
 Good resistance to tear.

**SAFETY**

Rolled edge stops drops and reinforces the gauntlet resistance to tear.

## Technical Description

**Description**

CE CATEGORY : III Irreversible risks  
 In accordance with standards :  
 EN 420-2003 EEC Basic standards  
 EN 388-2003 Mechanical risks  
 EN 374-2003 Chemical risks

**CHARACTERISTICS :**

Unsupported Butyl® glove  
 Rolled edge  
 Smooth inside

**Product Technology**

Dipped Gloves

**Glove/liner color**

Black

**Coating Type**

Rubber

**Length**

35 cm

**Thickness**

0.5 mm

**Harmlessness**

In conformity with the European standards

**Dexterity**

Class 5

**Sizes**

8 to 11

### EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	2
Cutting resistance	1
Tear resistance	1
Puncture resistance	1

### EN 374-3 Resistance to

Resistance to permeation by chemicals	BKL
---------------------------------------	-----

### Packaging Label

**Tagging**

CE0075 HONEYWELL  
 2008010 XX  
 EN 420  
 EN 388 : 2111  
 EN 374-3 : BKL

## Certifications

 E.C. Declaration of Conformity

**EC Category PPE**

3

**Quality Assurance**

ISO 9001 / 2000

**EC Attestation**

 EC Attestation

**EC Attestation Number**

0075/797/162/05/13/0411

## Additional Information

**User Manual**

UI 104

**User Information Sheet**

104

## Maintenance

**Storage Information**

Minimum packaging 10 pairs.

Cartons of 50 pairs.

**Care Instructions**

In order to keep its properties, this article should not be cleaned.